

DECLARATION OF CONFORMITY

Manufacturer: Procalçado - Produtora de Componentes para Calçado, S.A.
Largo das Alminhas das Barrancas, 97, 4415-343 Pedroso – PORTUGAL

General Requirements: Regulation 2016/425 – category 1

Model: CLOG



Description: Clog marked WOCK®, entirely made of polymeric materials, with two colors and a black antistatic insert, with strap and removable Steri-Tech® Clog insole.

Size range: From 35/36 to 47/48

Intended use: Hospitals and other Healthcare Institutions; Cosmetics/Beauty Companies; Pharmaceutical Industry; Operation Room.

Technical standard: EN ISO 20344:2011 - Personal protective equipment – Test methods for footwear
EN ISO 20347:2012 - Personal protective equipment – Occupational footwear

Technical features:

- Specific ergonomics features:** EN ISO 20347:2012/5.3.3 / EN ISO 20344:2011/5.1
- Thickness of upper:** EN ISO 20347:2012/5.4.2 / EN ISO 20344:2011/6.1
- Tensile properties of upper:** EN ISO 20347:2012/5.4.4 / EN ISO 20344:2011/6.4
- Flexing resistance of upper:** EN ISO 20347:2012/5.4.5 / EN ISO 20344:2011/6.5
- Tear strength of outsole:** EN ISO 20347:2012/5.8.2 / EN ISO 20344:2011/8.2
- Abrasion resistance of outsole:** EN ISO 20347:2012/5.8.3 / EN ISO 20344:2011/8.3
- Flexing resistance of outsole:** EN ISO 20347:2012/5.8.4 / EN ISO 20344:2011/8.4
- Antistatic footwear:** EN ISO 20347:2012/6.2.2.2 / EN ISO 20344:2011/5.10
- Energy absorption of seat region:** EN ISO 20347:2012 / 6.2.4 / EN ISO 20344:2011/5.14
- Slip resistance (dry and wet):** SATRA TM144:2011

Additional information: Washability at 90°C: SATRA TM 158:1992
Sterilization in Autoclavable after 5 cycles of 15 minutes at 134°C

Additional notes: WOCK® CLOG Walksoft Insole (sold separately) cannot be washed or sterilized in an autoclave; clogs lose their anti-static properties when insoles are worn.

Grijó, V. N. Gaia, Portugal

Managing Director

